

AZ800

- Super soft flexibility
- Nylon Reinforcement
- Two extra nylon overlays for advanced high speed durability with jointless technology
- Inner liner
- Super hard apex
- Two super steel belts provide high level of tire durability

- Dual-Layer tread Cap-Enhances superior traction on surfaces
- Base-New tread compound conquers heat build-up
- Two polyester carcass plies enhance casing strength for excellent resistance to road hazard damage (Some sizes only)
- High tensile bead wire wraps casing plies around the bead in opposite direction to combine good ride compliance with responsive steering and handling.

ATTURO

The Atturo AZ800 is an ultra high performance tyre designed for SUV and cross over applications. The directional tread pattern and aggressive sidewall style demonstrate the performance engineering beneath the surface.



Size	Speed Load Index	Overall Diameter		Section Width		Measuring Rim	Approved Rim Width	Tread Width		Tread Depth		MAX, PSI	Max Load		UTQG
		MM	Inches	MM	Inches			MM	Inches	MM	Inches		KG	LBS	
255/50R19	107W XL	739	29.1	264	10.4	8	7.0-9.0	223	8.8	8.6	11.00	42	975	2150	420.A.A
285/45R19	111W XL	739	29.1	287	11.3	9.5	9.0-10.5	242	9.5	8.5	11.00	44	975	2150	420.A.A
255/45R20	105V XL	738	29.1	255	10.0	8.5	8.0-9.0	216	8.5	8.90	11.2	50	925	2039	420.A.A
265/50R20	112V XL	774	30.5	265	10.4	8.5	8.0-9.0	233	9.2	8.50	10.7	42	1120	2469	420.A.A
275/60R20	119V XL	838	33.0	275	10.8	8.0	7.5-8.5	220	8.7	8.70	11.0	50	1180	2601	420.A.A
275/40R20	106W XL	728	28.7	278	10.9	9.5	9.0-10.0	237	9.3	9.00	11.3	44	950	2094	420.A.A
275/45R20	110V XL	773	30.4	297	11.7	10.0	9.5-10.5	252	9.9	8.20	10.3	50	1030	2271	420.A.A
315/35R20	106W	728	28.7	318	12.5	11.0	10.5-11.5	290	11.4	9.00	11.3	44	950	2094	420.A.A
235/30R22	90Y XL	701	27.6	241	9.5	8.5	8.0-9.0	230	9.1	11	8.5	50	600	1323	420.A.A
255/30R22	95Y XL	713	28.1	255	10	9	8.5-9.5	249	9.8	8.90	11.0	50	690	1522	420.A.A
265/35R22	102V XL	745	29.3	265	10.4	9.5	9.0-10.0	245	9.6	8.50	10.7	50	850	1874	420.A.A
285/35R22	106W XL	759	29.9	290	11.4	10.0	9.5-10.5	265	10.4	8.90	11.2	44	850	1874	420.A.A
295/30R22	103Y XL	737	29.0	195	7.7	10.5	10.0-11.0	277	10.9	8.90	11.2	50	875	1929	420.A.A
305/40R22	115V XL	803	31.6	305	12.0	11.0	10.5-11.5	260	10.2	8.60	10.8	50	1180	2601	420.A.A
305/45R22	118V XL	833	32.8	305	12.0	10.0	9.5-10.5	259	10.2	8.60	10.8	50	1320	2910	420.A.A
285/40R24	112V XL	846	33.3	291	11.4	10	9.5-11.0	243	9.6	8.4	11.0	50	1120	2464	420.A.A
295/40R24	114V XL	846	33.3	295	11.6	10.5	10.0-11.0	251	9.9	8.60	10.8	50	1180	2601	420.A.A
305/35R24	112V XL	824	32.4	305	12.0	11.0	10.5-11.5	290	11.4	8.60	10.8	50	1120	2469	420.A.A

ATURO

AZ800



 **Formula Distributors**

7205 Brown Street, Delta, BC, Canada, V4G 1G5

TOLL FREE: 1-800-663-5603

PH: 604-940-3399 FAX: 604-946-6827

fdlsales@aol.com formuladistributors.com

